

## MATRIZ CON VALONA SIN DESAHOGO PARA MECANIZAR RMBB

### MACHINABLE HEADED MATRIX COUNTERBORE RELIEF RMBB


Material / Material: 1.2379 HWS

Dureza / Hardness: 62 ±2HRC

STOCK



**i** También disponible en otros aceros y medidas bajo plano.  
Also available in other steels and dimensions per dwg.



Standard: ISO 8977 D

D m5	D1 <sup>0</sup> <sub>-2,5</sub>	L1 <sup>+1,5</sup> <sub>0</sub>	R	P	L <sup>+0,5</sup> <sub>0</sub>							
					20	22	25	28	30	32	35	40
8	11	4	4	1,2	•	•	•	•	•	•	•	•
10	13	4	6,0	1,2	•	•	•	•	•	•	•	•
13	16	5	8	1,4	•	•	•	•	•	•	•	•
16	19	5	9,5	2	•	•	•	•	•	•	•	•
20	23	5	12	2,8	•	•	•	•	•	•	•	•
22	25	6	15	2,8	•	•	•	•	•	•	•	•
25	28	6	17,5	4,4	•	•	•	•	•	•	•	•
32	35	6	21	5,2	•	•	•	•	•	•	•	•
38	41	8	27	5,6	•	•	•	•	•	•	•	•
40	43	8	27	5,6	•	•	•	•	•	•	•	•

How to order:

Specify	RMBB	D	L	Mat.
Example	RMBB	10	20	HWS
	RMBB	32	30	HWS