

MATRIZ CON VALONA RMSB HEADED MATRIX RMSB


Material: 1.2379 HWS
Dureza / Hardness: 62 ±2HRC

STOCK

Material / Material: 1.3343 HSS
Dureza / Hardness: 64 ±2HRC



i También disponible en otros aceros y medidas bajo plano.
Also available in other steels and dimensions per dwg.



Standard: DIN 9845 B

D1 ^{H8}	$\begin{matrix} +0,3 \\ L \\ 0 \end{matrix}$		D ^{k6}	D3	R ^{±0,1}	L1	r
1	20	28	5	7	D1+0,3	2	0,3
1,1 - 2	20	28	6	8	D1+0,3	3	0,3
2,1 - 3	20	28	7	9	D1+0,5	3	0,4
3,1 - 4	20	28	8	10	D1+0,5	3	0,4
4,1 - 5	20	28	10	12	D1+0,7	4	0,4
5,1 - 6	20	28	12	14	D1+0,7	4	0,6
6,1 - 8	20	28	15	17	D1+0,7	4	0,8
8,1 - 10	20	28	18	20	D1+1	4	0,8
10,1 - 12	20	28	22	24	D1+1	5	0,8
12,1 - 15	20	28	26	28	D1+1	5	0,8

How to order:

Specify	RMSB	D1	L	Mat.
Example	RMSB	10	20	HSS
	RMSB	5	28	HWS